



27"

Display Module

Touch Monitor

Box Module

Box Module	
I/O	DVI-I *1
	USB *1 (For Touch)
	VGA *1
	HDMI 1.4a *1
	DisplayPort 1.2 *1
	Line Out *1
	Locking DC *1
Touch screen	Projected Capacitive Touch
Power Requirement	DC Jack, +24V Input
Mechanical	
Construction	Heavy-duty steel chassis (Black)
Operation Temp.	32°F ~ 140°F (0°C ~ 60°C) with Ambient Air
Storage Temp.	-22°F ~ 175°F (-30°C ~ 80°C)
Relative Humidity	10~90% @40°C, Non-condensing
Vibration	5-17Hz, 0.1" double amplitude peak to peak, 1.5G acceleration peak to peak
Shock	10G acceleration peak to peak (11ms)
Qualification	Formal certification CE I FCC Class B
Optional Order	
USB Cable	180mm/300mm USB Cable
DVI Cable	180mm/300mm DVI Cable
HDMI Cable	180mm/300mm DVI Cable
DisplayPort Cable	180mm/300mm DisplayPort Cable
VGA Cable	180mm/300mm VGA Cable
Mounting	Clamp Type Mount

Display Module	
I/O	1x USB 2.0 Hidden for USB Dongle
Touch screen	Projected Capacitive Touch
LCD	27" TFT XGA
Resolution	1920*1080, 16.2M Colors
Luminance (cd/m2)	300
Viewing Angle	178°
Backlight Lifetime	30,000hrs / LED
Mechanical	
Construction	Heavy-duty steel chassis (Black), Aluminum Front
Rating	IP 65 compliant front bezel
Mounting	Panel / VESA 100 / Wall / Clamp Type
Optional Order	
Mounting	Clamp Type Mounting Kit

Display Module and Box Module	
Dimension	649.4mm*55mm*387.4mm
Packing Dimension	790mm*220mm*590mm
System Weight(N.W.)	8.5 KG
Weight with Packing(G.W.)	9.7 KG