



# 15"

## Open Frame Display Module

# Touch Monitor

## Box Module

| Box Module        |                                                                            |
|-------------------|----------------------------------------------------------------------------|
| I/O               | DVI-I *1                                                                   |
|                   | USB *1 (For Touch)                                                         |
|                   | VGA *1                                                                     |
|                   | HDMI 1.4a *1                                                               |
|                   | DisplayPort 1.2 *1                                                         |
|                   | Line Out *1                                                                |
|                   | Locking DC *1                                                              |
| Touch screen      | Projected Capacitive Touch                                                 |
| Power Requirement | DC Jack, +24V Input                                                        |
| Mechanical        |                                                                            |
| Construction      | Heavy-duty steel chassis (Black)                                           |
| Operation Temp.   | 32°F ~ 140°F (0°C ~ 60°C) with Ambient Air                                 |
| Storage Temp.     | -22°F ~ 175°F (-30°C ~ 80°C)                                               |
| Relative Humidity | 10~90% @40°C, Non-condensing                                               |
| Vibration         | 5-17Hz, 0.1" double amplitude peak to peak, 1.5G acceleration peak to peak |
| Shock             | 10G acceleration peak to peak (11ms)                                       |
| Qualification     | Formal certification CE I FCC Class B                                      |
| Optional Order    |                                                                            |
| USB Cable         | 180mm/300mm USB Cable                                                      |
| DVI Cable         | 180mm/300mm DVI Cable                                                      |
| HDMI Cable        | 180mm/300mm DVI Cable                                                      |
| DisplayPort Cable | 180mm/300mm DisplayPort Cable                                              |
| VGA Cable         | 180mm/300mm VGA Cable                                                      |
| Mounting          | Clamp Type Mount                                                           |

| Display Module     |                                                  |
|--------------------|--------------------------------------------------|
| I/O                | 1x USB 2.0 Hidden for USB Dongle                 |
| Touch screen       | Projected Capacitive Touch                       |
| LCD                | 15" TFT XGA                                      |
| Resolution         | 1024*768, 16.2M Colors                           |
| Luminance (cd/m2)  | 250                                              |
| Viewing Angle      | 80°                                              |
| Backlight Lifetime | 50,000hrs / LED                                  |
| Mechanical         |                                                  |
| Construction       | Heavy-duty steel chassis (Black), Aluminum Front |
| Rating             | IP 65 compliant front bezel                      |
| Mounting           | Panel / VESA 100 / Wall / Clamp Type             |
| Optional Order     |                                                  |
| Mounting           | Clamp Type Mounting Kit                          |